


# LIQ FUSION



- ▀ **Exclusive RGB-sync waterblock with patented flow indicator design**
- ▀ **Support the latest addressable RGB M/B sync**
- ▀ **Integrated RGB control box**
- ▀ **High-efficiency ceramic bearing pump for exceptional durability and noiseless operation**



LIQFUSION, an individually addressable RGB liquid cooler for Intel and AMD CPU platforms, is built with an exclusive RGB-sync water-block featuring patented flow indicator, which enables the user to easily monitor the status of coolant flow. Together with visually appealing ENERMAX addressable RGB fans, LIQFUSION can create unique, vivid RGB lighting effects. The addressable RGB water cooler is designed to sync the RGB lighting with selected GIGABYTE, MSI and ASROCK motherboards with addressable RGB headers. Meanwhile, LIQFUSION also includes integrated RGB control box for non RGB-Sync motherboards.

## Features

- ▀ **Patented flow indicator design**  
Patented flow indicator allows users to visually monitor cooling loop operation and coolant level



- ▀ **Addressable RGB lighting synchronization**  
Synchronizable RGB Lighting via the latest addressable RGB header of motherboards (the RGB header 4-Pin assignment is +5V/D/-/G)

- ▀ **ENERMAX T.B. RGB™ fans**  
ENERMAX T.B. RGB™ fans support the latest addressable RGB-sync function to provide an incredible RGB lighting experience



- ENERMAX integrated RGB control box  
ENERMAX integrated RGB control box enables users to adjust preferred lighting effects (14 pre-set effects), colors and speed



- High-efficiency ceramic pump with rubber cover  
The pump is attached to the rubber tubes for optimum vibration damping and silent operation

- 240mm radiator  
Micro fiber channels and large cooling surface for high performance with up to 300W TDP



- Premium 400mm weaved tubing is perfect for mainstream system builds

- Universal metal mounting kits  
Support the latest Intel® and AMD® sockets for easy and solid installation (excluding TR4/SP3 socket)





**Dow corning® TC5121 thermal grease**

## Specifications

<b>Model Number</b>		<b>ELC-LF240-RGB</b>
<b>CPU Socket</b>		Intel® LGA 2066/2011-3/2011/1366/1156/1155/1151/1150/775 AMD® AM4/AM3+/AM3/AM2+/AM2/FM2+/FM2/FM1
<b>Material</b>		Copper base with Aluminum Radiator
<b>Pump</b>	<b>Bearing</b>	Ceramic bearing
	<b>MTBF</b>	50,000 hrs
	<b>Rated Voltage</b>	12V
	<b>Rated Current</b>	0.18A
<b>Fan</b>	<b>Dimension</b>	120 x 120 x 25 mm
	<b>Bearing</b>	Twister Bearing
	<b>MTBF</b>	≥ 160000 hrs
	<b>Speed</b>	500 - 2000 RPM (±10%)
	<b>Rated Voltage</b>	12V
	<b>Rated Current</b>	0.3A
	<b>Air Flow</b>	23.81 ~ 102.17 CFM
		40.45 ~ 173.59 m³/h
	<b>Static Pressure</b>	0.673 ~ 6.28 mm-H <sub>2</sub> O
	<b>Noise Level</b>	14 ~ 28 dBA
<b>Connector</b>	4 Pin PWM + 4 Pin RGB	
<b>Thermal Grease</b>		Dow Corning® TC-5121
<b>Maintenance Kit</b>		100ml coolant, 1g thermal grease
<b>Shipping information</b>		
<b>Barcode</b>	<b>EAN</b>	4713157723383
	<b>UPC</b>	819315023389
<b>Box Dimension</b>		332x243x139mm
<b>Gross Weight / unit</b>		1.99kgs
<b>Carton Dimension</b>		578x502x360mm
<b>Q'ty / carton</b>		8PCS
<b>Gross Weight / Carton</b>		15.92kgs