

## TP-Link Archer C50 draadloze router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) Zwart

**Merk :** TP-Link

**Artikelcode:** ARCHER C50 V1

**Productnaam :** Archer C50

TP-Link Archer C50. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 5 (802.11ac), Wi-Fi-standaarden: 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n). Interfacetype Ethernet LAN: Fast Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100 Mbit/s, VPN eigenschappen: PPTP, L2TP, IPSec. Ondersteunde beveiligingsalgoritmen: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Type product: Router om neer te zetten, Kleur van het product: Zwart. Meegeleverde kabels: LAN (RJ-45)



<b>WAN-verbinding</b>		<b>Beveiliging</b>	
Ethernet WAN *	✓	Filtratie	✓
<b>Draadloos LAN</b>		MAC adres filtering	✓
Wifi-band *	Dual-band (2.4 GHz / 5 GHz)	IP-adresfilter	✓
Wifi-standaard *	Wi-Fi 5 (802.11ac)	DMZ support	✓
Wi-Fi-standaarden	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	<b>Protocollen</b>	
WLAN gegevensoverdrachtsnelheid (eerste band)	300 Mbit/s	DHCP client	✓
WLAN gegevensoverdrachtsnelheid (tweede band)	867 Mbit/s	DHCP server	✓
<b>Netwerk</b>		Universal Plug and Play ( UPnP )	✓
Ethernet LAN *	✓	<b>Design</b>	
Interfacetype Ethernet LAN *	Fast Ethernet	Kleur van het product	Zwart
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Aan/uitschakelaar	✓
Port forwarding	✓	Type product *	Router om neer te zetten
VPN eigenschappen	PPTP, L2TP, IPSec	<b>Inhoud van de verpakking</b>	
<b>Poorten &amp; interfaces</b>		Meegeleverde kabels	LAN (RJ-45)
Aantal Ethernet LAN (RJ-45)-poorten *	4	Inclusief AC-adapter	✓
USB-poort *	✓	Snelstartgids	✓
Aantal USB 2.0-poorten	1	<b>Antenne</b>	
<b>Beheerfuncties</b>		Antenne-ontwerp *	Extern
Quality of Service (QoS)	✓	Antennas quantity	2
Reset button	✓	<b>Energie</b>	
WPS Push Button Security	✓	Type stroombron *	AC
<b>Beveiliging</b>		<b>Eisen aan de omgeving</b>	
Ondersteunde beveiligingsalgoritmen	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Bedrijfstemperatuur (T-T)	0 - 40 °C
Firewall	✓	Temperatuur bij opslag	-40 - 70 °C
Stateful Packet Inspection (SPI)	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
DoS aanval preventie	✓	Luchtvochtigheid bij opslag	5 - 90 procent
		<b>Gewicht en omvang</b>	
		Breedte	182,9 mm
		Diepte	123,5 mm
		Hoogte	32,1 mm



6935364091675

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date