

TP-Link Archer T2U WLAN 600 Mbit/s

Merk : TP-Link

Artikelcode: ARCHER T2U V2

Productnaam : Archer T2U

AC600 Draadloze dual-band USB-adapter

TP-Link Archer T2U. Connectiviteitstechnologie: Draadloos, Hostinterface: USB, Interface: WLAN.

Maximale overdrachtssnelheid van gegevens: 600 Mbit/s, Wifi-standaard: Wi-Fi 5 (802.11ac), Wifi-band:

Dual-band (2.4 GHz / 5 GHz). Kleur van het product: Zwart



Poorten & interfaces		Design	
Connectiviteitstechnologie *	Draadloos		5GHz □ 11a 6Mbps: -94dBm 11a 54Mbps: -78dBm 11n HT20 MCS0: -94dBm 11n HT20 MCS7: -77dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -74dBm 11ac VHT80 MCS0: -89dBm 11ac VHT80 MCS9: -64dBm 2.4GHz: 11b 1Mbps: -99dBm 11b 11Mbps: -91dBm 11g 6Mbps: -94dBm 11g 54Mbps: -77dBm 11n HT20 MCS0: -95dBm 11n HT20 MCS7: -76dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -73dBm
Hostinterface *	USB		
Interface *	WLAN		
USB-versie	2.0		
Netwerk		Gevoeligheid ontvanger	
Maximale overdrachtssnelheid van gegevens *	600 Mbit/s		
Netwerkstandaard *	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ac	Certificering	CE, FCC
Wifi	✓	Minimale systeemeisen	
Wifi-band	Dual-band (2.4 GHz / 5 GHz)	CD-ROM drive	✓
Frequentiebereik	2,4 - 5 GHz	Ondersteunt Windows	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows XP
Wifi-standaard	Wi-Fi 5 (802.11ac)	Ondersteunt Mac-besturingssysteem	macOS
Wi-Fi-standaarden	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Ondersteunt Linux	✓
Ondersteunde WLAN data-overdrachtsnelheden	11,54,150,433,600 Mbit/s	Eisen aan de omgeving	
Modulatie	16-QAM, 256-QAM, 64-QAM, CCK, DBPSK, DQPSK, OFDM	Bedrijfstemperatuur (T-T)	0 - 40 °C
Ondersteunde beveiligingsalgoritmen	128-bit WEP, 64-bit WEP, 802.1x RADIUS, WPA, WPA2, WPA2-AES, WPA2-PSK, WPA2-TKIP, WPS	Temperatuur bij opslag	-40 - 70 °C
Design		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Component voor *	PC/Laptop	Luchtvochtigheid bij opslag	5 - 90 procent
Kleur van het product	Zwart	Gewicht en omvang	
Intern *	✗	Breedte	40,5 mm
Antenne	✓	Diepte	19,7 mm
Antenne-ontwerp	Intern	Hoogte	10,3 mm

Design		Verpakking	
LED-indicatoren	Status	Aantal	1
		Breedte verpakking	138 mm
		Diepte verpakking	128 mm
		Hoogte verpakking	30 mm
		Gewicht verpakking	90 g
Technische details			
		Certificaten van naleving	RoHS
Logistieke gegevens			
		Code geharmoniseerd systeem (HS)	85176990
Overige specificaties			
		Snelstartgids	✓



6935364050856



6935364080099



8944467768825

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.